



ALL ALUMINIUM ALLOY CONDUCTOR

IEC 61089 / ASTM B399

14 orderable sizes

STANDARD IEC 61089 / ASTM B399	CONDUCTOR All aluminium alloy conductor	INSULATION / JACKET Bare conductor
------------------------------------------	---------------------------------------------------	----------------------------------------------

Construction

- 1 Conductor – Aluminium alloy conductor · 7 × Ø2.52 mm · IEC 60228 cl.2

Size selection — all available cross-sections

Cable reference	Conductor size	Stranding	Nominal diameter	Max DC resistance at 20 °C	Rated strength guide	Weight guide	Standard reference
AAAC all aluminium alloy conductor IEC 61089 AAAC 16 mm ²	16 mm ²	7 aluminium wires	4.88 mm	1.91 Ω/km	1.9 kN	43 kg/km	IEC 61089 AAAC
AAAC all aluminium alloy conductor IEC 61089 AAAC 25 mm ²	25 mm ²	7 aluminium wires	6.10 mm	1.22 Ω/km	3 kN	68 kg/km	IEC 61089 AAAC
AAAC all aluminium alloy conductor IEC 61089 AAAC 35 mm ²	35 mm ²	7 aluminium wires	7.22 mm	0.87 Ω/km	4.2 kN	95 kg/km	IEC 61089 AAAC
AAAC all aluminium alloy conductor IEC 61089 AAAC 50 mm ²	50 mm ²	19 aluminium wires	8.63 mm	0.61 Ω/km	6 kN	135 kg/km	IEC 61089 AAAC
AAAC all aluminium alloy conductor IEC 61089 AAAC 70 mm ²	70 mm ²	19 aluminium wires	10.21 mm	0.44 Ω/km	8.4 kN	189 kg/km	IEC 61089 AAAC
AAAC all aluminium alloy conductor IEC 61089 AAAC 95 mm ²	95 mm ²	19 aluminium wires	11.89 mm	0.32 Ω/km	11.4 kN	257 kg/km	IEC 61089 AAAC
AAAC all aluminium alloy conductor IEC 61089 AAAC 120 mm ²	120 mm ²	19 aluminium wires	13.4 mm	0.254 Ω/km	14.4 kN	324 kg/km	IEC 61089 AAAC
AAAC all aluminium alloy conductor IEC 61089 AAAC 150 mm ²	150 mm ²	19 aluminium wires	14.9 mm	0.204 Ω/km	18 kN	405 kg/km	IEC 61089 AAAC

Cable reference	Conductor size	Stranding	Nominal diameter	Max DC resistance at 20 °C	Rated strength guide	Weight guide	Standard reference
AAAC all aluminium alloy conductor IEC 61089 AAAC 185 mm ²	185 mm ²	37 or 61 aluminium wires	16.6 mm	0.165 Ω/km	22.2 kN	500 kg/km	IEC 61089 AAAC
AAAC all aluminium alloy conductor IEC 61089 AAAC 240 mm ²	240 mm ²	37 or 61 aluminium wires	18.9 mm	0.127 Ω/km	28.8 kN	648 kg/km	IEC 61089 AAAC
AAAC all aluminium alloy conductor IEC 61089 AAAC 300 mm ²	300 mm ²	37 or 61 aluminium wires	21.1 mm	0.102 Ω/km	36 kN	810 kg/km	IEC 61089 AAAC
AAAC all aluminium alloy conductor IEC 61089 AAAC 400 mm ²	400 mm ²	37 or 61 aluminium wires	24.4 mm	0.076 Ω/km	48 kN	1080 kg/km	IEC 61089 AAAC
AAAC all aluminium alloy conductor IEC 61089 AAAC 500 mm ²	500 mm ²	37 or 61 aluminium wires	27.3 mm	0.061 Ω/km	60 kN	1350 kg/km	IEC 61089 AAAC
AAAC all aluminium alloy conductor IEC 61089 AAAC 630 mm ²	630 mm ²	37 or 61 aluminium wires	30.6 mm	0.048 Ω/km	75.6 kN	1701 kg/km	IEC 61089 AAAC

UE Cable · China — sales@uecable.com · uecable.com Confirm colour, printing, packing length, delivery country and test documents on enquiry.