



### BESS COMMUNICATION AND MONITORING CABLE

IEC 61158

9 orderable sizes

STANDARD <b>IEC 61158</b>	VOLTAGE CLASS <b>Signal circuit</b>	CONDUCTOR <b>Tinned copper data conductor</b>
INSULATION / JACKET <b>LSZH, PUR or PE jacket</b>		

#### Construction

- 1 ■ **Conductor (per core)** – Flexible copper conductor · 24 × Ø0.2 mm · IEC 60228 cl.5
- 2 ■ **Pair insulation** – PE, foam PE or LSZH data insulation
- 3 ■ **Filler** – Bedding / filler
- 4 ■ **Sheath** – LSZH, PUR or PE jacket

#### Size selection — all available cross-sections

Cable reference	System position	Voltage class	Current guide	Conductor size	Polarity / ID	Environment
<b>BESS Monitoring Data Signal circuit 1 pair 0.5 mm<sup>2</sup> Pair color ID</b>	Monitoring and communication	Signal circuit	3 A layout-dependent	0.5 mm <sup>2</sup>	Pair color ID	CAN, RS-485, sensor and monitoring network duty
<b>BESS Monitoring Data Signal circuit 1 pair 0.75 mm<sup>2</sup> Pair color ID</b>	Monitoring and communication	Signal circuit	4 A layout-dependent	0.75 mm <sup>2</sup>	Pair color ID	CAN, RS-485, sensor and monitoring network duty
<b>BESS Monitoring Data Signal circuit 1 pair 1.0 mm<sup>2</sup> Pair color ID</b>	Monitoring and communication	Signal circuit	5 A layout-dependent	1.0 mm <sup>2</sup>	Pair color ID	CAN, RS-485, sensor and monitoring network duty
<b>BESS Monitoring Data Signal circuit 2 pair 0.5 mm<sup>2</sup> Pair color ID</b>	Monitoring and communication	Signal circuit	3 A layout-dependent	0.5 mm <sup>2</sup>	Pair color ID	CAN, RS-485, sensor and monitoring network duty
<b>BESS Monitoring Data Signal circuit 2 pair 0.75 mm<sup>2</sup> Pair color ID</b>	Monitoring and communication	Signal circuit	4 A layout-dependent	0.75 mm <sup>2</sup>	Pair color ID	CAN, RS-485, sensor and monitoring network duty

Cable reference	System position	Voltage class	Current guide	Conductor size	Polarity / ID	Environment
<b>BESS Monitoring Data Signal circuit 2 pair 1.0 mm<sup>2</sup> Pair color ID</b>	Monitoring and communication	Signal circuit	5 A layout-dependent	1.0 mm <sup>2</sup>	Pair color ID	CAN, RS-485, sensor and monitoring network duty
<b>BESS Monitoring Data Signal circuit 4 pair 0.5 mm<sup>2</sup> Pair color ID</b>	Monitoring and communication	Signal circuit	3 A layout-dependent	0.5 mm <sup>2</sup>	Pair color ID	CAN, RS-485, sensor and monitoring network duty
<b>BESS Monitoring Data Signal circuit 4 pair 0.75 mm<sup>2</sup> Pair color ID</b>	Monitoring and communication	Signal circuit	4 A layout-dependent	0.75 mm <sup>2</sup>	Pair color ID	CAN, RS-485, sensor and monitoring network duty
<b>BESS Monitoring Data Signal circuit 4 pair 1.0 mm<sup>2</sup> Pair color ID</b>	Monitoring and communication	Signal circuit	5 A layout-dependent	1.0 mm <sup>2</sup>	Pair color ID	CAN, RS-485, sensor and monitoring network duty

UE Cable · China — sales@uecable.com · uecable.com Confirm colour, printing, packing length, delivery country and test documents on enquiry.