



INDIVIDUAL AND OVERALL SCREENED

EN 50288-7

28 orderable sizes

STANDARD EN 50288-7	VOLTAGE CLASS 300/500 V or 500 V application reference	CONDUCTOR 0.5 mm ² , 0.75 mm ² , 1.0 mm ² , 1.5 mm ² and customer- specified sizes
INSULATION / JACKET PVC	CROSS-SECTION RANGE 2 pair to 50 pair available range	

Construction

- 1 ■ Conductor (per core) – Bare or tinned annealed copper conductor · 1 × Ø1.13 mm · IEC 60228 cl.1
- 2 ■ Pair insulation – PE
- 3 ■ Individual screen (IS) – Al/polyester foil + tinned-copper drain
- 4 ■ Filler – Bedding / filler
- 5 ■ Overall screen (OS) – Al/polyester foil + drain
- 6 ■ Sheath – PVC

Size selection — all available cross-sections

Cable reference	Pair / triple / core layout	Conductor size	Conductor class	Max DC resistance at 20 °C	Mutual capacitance	L/R ratio	OD guide	Weight guide
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-2PAIR-ØP5MM2 2 pair 0.5 mm ²	2 pair	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	9.1 mm	90 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-2PAIR-ØP75MM2 2 pair 0.75 mm ²	2 pair	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	9.3 mm	99 kg/km

Cable reference	Pair / triple / core layout	Conductor size	Conductor class	Max DC resistance at 20 °C	Mutual capacitance	L/R ratio	OD guide	Weight guide
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-2PAIR-1P0MM2 2 pair 1.0 mm ²	2 pair	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	115 pF/m guide	40 uH/ohm	9.5 mm	108 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-2PAIR-1P5MM2 2 pair 1.5 mm ²	2 pair	1.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	115 pF/m guide	40 uH/ohm	9.7 mm	126 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-5PAIR-0P5MM2 5 pair 0.5 mm ²	5 pair	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	10.5 mm	133 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-5PAIR-0P75MM2 5 pair 0.75 mm ²	5 pair	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	10.6 mm	155 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-5PAIR-1P0MM2 5 pair 1.0 mm ²	5 pair	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	120 pF/m guide	40 uH/ohm	10.8 mm	177 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-5PAIR-1P5MM2 5 pair 1.5 mm ²	5 pair	1.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	120 pF/m guide	40 uH/ohm	11.0 mm	222 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-10PAIR-0P5MM2 10 pair 0.5 mm ²	10 pair	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	12.0 mm	203 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-10PAIR-0P75MM2 10 pair 0.75 mm ²	10 pair	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	12.1 mm	248 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-10PAIR-1P0MM2 10 pair 1.0 mm ²	10 pair	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	120 pF/m guide	40 uH/ohm	12.3 mm	292 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-10PAIR-1P5MM2 10 pair 1.5 mm ²	10 pair	1.5 mm ²	Class 1 (solid) / 2 (stranded)	13.43 Ω/km	120 pF/m guide	40 uH/ohm	12.5 mm	381 kg/km

Cable reference	Pair / triple / core layout	Conductor size	Conductor class	Max DC resistance at 20 °C	Mutual capacitance	L/R ratio	OD guide	Weight guide
			/ 5 (flexible)					
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-15PAIR-0P5MM2 15 pair 0.5 mm ²	15 pair	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	13.1 mm	274 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-15PAIR-0P75MM2 15 pair 0.75 mm ²	15 pair	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	13.3 mm	340 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-15PAIR-1P0MM2 15 pair 1.0 mm ²	15 pair	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	120 pF/m guide	40 uH/ohm	13.4 mm	407 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-15PAIR-1P5MM2 15 pair 1.5 mm ²	15 pair	1.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	120 pF/m guide	40 uH/ohm	13.7 mm	541 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-20PAIR-0P5MM2 20 pair 0.5 mm ²	20 pair	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	14.1 mm	344 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-20PAIR-0P75MM2 20 pair 0.75 mm ²	20 pair	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	14.3 mm	433 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-20PAIR-1P0MM2 20 pair 1.0 mm ²	20 pair	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	120 pF/m guide	40 uH/ohm	14.4 mm	522 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-20PAIR-1P5MM2 20 pair 1.5 mm ²	20 pair	1.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	120 pF/m guide	40 uH/ohm	14.7 mm	700 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-30PAIR-0P5MM2 30 pair 0.5 mm ²	30 pair	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	15.7 mm	485 kg/km

Cable reference	Pair / triple / core layout	Conductor size	Conductor class	Max DC resistance at 20 °C	Mutual capacitance	L/R ratio	OD guide	Weight guide
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-30PAIR-0P75MM2 30 pair 0.75 mm ²	30 pair	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	15.9 mm	619 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-30PAIR-1P0MM2 30 pair 1.0 mm ²	30 pair	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	120 pF/m guide	40 uH/ohm	16.0 mm	752 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-30PAIR-1P5MM2 30 pair 1.5 mm ²	30 pair	1.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	120 pF/m guide	40 uH/ohm	16.3 mm	1019 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-50PAIR-0P5MM2 50 pair 0.5 mm ²	50 pair	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	18.3 mm	767 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-50PAIR-0P75MM2 50 pair 0.75 mm ²	50 pair	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	18.5 mm	990 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-50PAIR-1P0MM2 50 pair 1.0 mm ²	50 pair	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	120 pF/m guide	40 uH/ohm	18.6 mm	1212 kg/km
UEC-EN50288-7-PE-PVC-IOS-MULTIPAIR-50PAIR-1P5MM2 50 pair 1.5 mm ²	50 pair	1.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	120 pF/m guide	40 uH/ohm	18.9 mm	1657 kg/km