



OVERALL SCREENED

EN 50288-7

4 orderable sizes

| | | |
|-----------------------------------|--|--|
| STANDARD EN 50288-7 | VOLTAGE CLASS 300/500 V or 500 V application reference | CONDUCTOR 0.5 mm², 0.75 mm², 1.0 mm², 1.5 mm² and customer-specified sizes |
| INSULATION / JACKET PVC | CROSS-SECTION RANGE 1 triple | |

Construction

- 1 ■ Conductor (per core) – Bare or tinned annealed copper conductor · 1 × Ø1.13 mm · IEC 60228 cl.1
- 2 ■ Triad insulation – PE
- 3 ■ Filler – Bedding / filler
- 4 ■ Overall screen (OS) – Al/polyester foil + drain
- 5 ■ Sheath – PVC

Size selection — all available cross-sections

| Cable reference | Pair / triple / core layout | Conductor size | Conductor class | Max DC resistance at 20 °C | Mutual capacitance | L/R ratio | OD guide | Weight guide |
|---|-----------------------------|----------------------|---|----------------------------|--------------------|-----------|----------|--------------|
| UEC-EN50288-7-PE-PVC-OS-SINGLE-TRIPLE-1TRIPLE-0P5MM2 1 triple 0.5 mm ² | 1 triple | 0.5 mm ² | Class 1 (solid) / 2 (stranded) / 5 (flexible) | 39.39 Ω/km | 75 pF/m guide | 25 uH/ohm | 7.9 mm | 72 kg/km |
| UEC-EN50288-7-PE-PVC-OS-SINGLE-TRIPLE-1TRIPLE-0P75MM2 1 triple 0.75 mm ² | 1 triple | 0.75 mm ² | Class 1 (solid) / 2 (stranded) / 5 (flexible) | 26.8 Ω/km | 75 pF/m guide | 25 uH/ohm | 8.1 mm | 79 kg/km |
| UEC-EN50288-7-PE-PVC-OS-SINGLE-TRIPLE-1TRIPLE-1P0MM2 1 triple 1.0 mm ² | 1 triple | 1.0 mm ² | Class 1 (solid) / 2 (stranded) / 5 (flexible) | 19.7 Ω/km | 85 pF/m guide | 40 uH/ohm | 8.3 mm | 85 kg/km |

| Cable reference | Pair / triple / core layout | Conductor size | Conductor class | Max DC resistance at 20 °C | Mutual capacitance | L/R ratio | OD guide | Weight guide |
|---|-----------------------------|---------------------|---|----------------------------|--------------------|-----------|----------|--------------|
| UEC-EN50288-7-PE-PVC-OS-SINGLE-TRIPLE-1TRIPLE-1P5MM2 1 triple 1.5 mm ² | 1 triple | 1.5 mm ² | Class 1 (solid) / 2 (stranded) / 5 (flexible) | 13.43 Ω/km | 85 pF/m guide | 40 uH/ohm | 8.6 mm | 99 kg/km |

UE Cable · China — sales@uecable.com · uecable.com Confirm colour, printing, packing length, delivery country and test documents on enquiry.