



## COPPER WIRE BRAID SCREENED

EN 50288-7

28 orderable sizes

<b>STANDARD</b> EN 50288-7	<b>VOLTAGE CLASS</b> 300/500 V or 500 V application reference	<b>CONDUCTOR</b> 0.5 mm <sup>2</sup> , 0.75 mm <sup>2</sup> , 1.0 mm <sup>2</sup> , 1.5 mm <sup>2</sup> and customer- specified sizes
<b>INSULATION / JACKET</b> PVC	<b>CROSS-SECTION RANGE</b> 2 pair to 50 pair available range	

### Construction

- 1 ■ Conductor (per core) – Bare or tinned annealed copper conductor · 1 × Ø1.13 mm · IEC 60228 cl.1
- 2 ■ Pair insulation – PVC
- 3 ■ Filler – Bedding / filler
- 4 ■ Overall screen (OS) – Al/polyester foil + drain
- 5 ■ Sheath – PVC

### Size selection — all available cross-sections

Cable reference	Pair / triple / core layout	Conductor size	Conductor class	Max DC resistance at 20 °C	Mutual capacitance	L/R ratio	OD guide	Weight guide
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-2PAIR-ØP5MM2 2 pair 0.5 mm <sup>2</sup>	2 pair	0.5 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	8.8 mm	101 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-2PAIR-ØP75MM2 2 pair 0.75 mm <sup>2</sup>	2 pair	0.75 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	9.0 mm	110 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-2PAIR-1PØMM2 2 pair 1.0 mm <sup>2</sup>	2 pair	1.0 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	115 pF/m guide	40 uH/ohm	9.2 mm	119 kg/km

Cable reference	Pair / triple / core layout	Conductor size	Conductor class	Max DC resistance at 20 °C	Mutual capacitance	L/R ratio	OD guide	Weight guide
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-2PAIR-1P5MM2 2 pair 1.5 mm <sup>2</sup>	2 pair	1.5 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	115 pF/m guide	40 uH/ohm	9.4 mm	136 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-5PAIR-0P5MM2 5 pair 0.5 mm <sup>2</sup>	5 pair	0.5 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	10.2 mm	135 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-5PAIR-0P75MM2 5 pair 0.75 mm <sup>2</sup>	5 pair	0.75 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	10.3 mm	157 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-5PAIR-1P0MM2 5 pair 1.0 mm <sup>2</sup>	5 pair	1.0 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	120 pF/m guide	40 uH/ohm	10.5 mm	180 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-5PAIR-1P5MM2 5 pair 1.5 mm <sup>2</sup>	5 pair	1.5 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	120 pF/m guide	40 uH/ohm	10.7 mm	224 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-10PAIR-0P5MM2 10 pair 0.5 mm <sup>2</sup>	10 pair	0.5 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	11.7 mm	192 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-10PAIR-0P75MM2 10 pair 0.75 mm <sup>2</sup>	10 pair	0.75 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	11.8 mm	237 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-10PAIR-1P0MM2 10 pair 1.0 mm <sup>2</sup>	10 pair	1.0 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	120 pF/m guide	40 uH/ohm	12.0 mm	281 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-10PAIR-1P5MM2 10 pair 1.5 mm <sup>2</sup>	10 pair	1.5 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	120 pF/m guide	40 uH/ohm	12.2 mm	370 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-15PAIR-0P5MM2 15 pair 0.5 mm <sup>2</sup>	15 pair	0.5 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	12.8 mm	249 kg/km

Cable reference	Pair / triple / core layout	Conductor size	Conductor class	Max DC resistance at 20 °C	Mutual capacitance	L/R ratio	OD guide	Weight guide
			/ 5 (flexible)					
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-15PAIR-0P75MM2 15 pair 0.75 mm <sup>2</sup>	15 pair	0.75 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	13.0 mm	316 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-15PAIR-1P0MM2 15 pair 1.0 mm <sup>2</sup>	15 pair	1.0 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	120 pF/m guide	40 uH/ohm	13.1 mm	383 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-15PAIR-1P5MM2 15 pair 1.5 mm <sup>2</sup>	15 pair	1.5 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	120 pF/m guide	40 uH/ohm	13.4 mm	516 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-20PAIR-0P5MM2 20 pair 0.5 mm <sup>2</sup>	20 pair	0.5 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	13.8 mm	306 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-20PAIR-0P75MM2 20 pair 0.75 mm <sup>2</sup>	20 pair	0.75 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	14.0 mm	395 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-20PAIR-1P0MM2 20 pair 1.0 mm <sup>2</sup>	20 pair	1.0 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	120 pF/m guide	40 uH/ohm	14.1 mm	484 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-20PAIR-1P5MM2 20 pair 1.5 mm <sup>2</sup>	20 pair	1.5 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	120 pF/m guide	40 uH/ohm	14.4 mm	662 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-30PAIR-0P5MM2 30 pair 0.5 mm <sup>2</sup>	30 pair	0.5 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	15.4 mm	420 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-30PAIR-0P75MM2 30 pair 0.75 mm <sup>2</sup>	30 pair	0.75 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	15.6 mm	554 kg/km

Cable reference	Pair / triple / core layout	Conductor size	Conductor class	Max DC resistance at 20 °C	Mutual capacitance	L/R ratio	OD guide	Weight guide
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-30PAIR-1P0MM2 30 pair 1.0 mm <sup>2</sup>	30 pair	1.0 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	120 pF/m guide	40 uH/ohm	15.7 mm	687 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-30PAIR-1P5MM2 30 pair 1.5 mm <sup>2</sup>	30 pair	1.5 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	120 pF/m guide	40 uH/ohm	16.0 mm	954 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-50PAIR-0P5MM2 50 pair 0.5 mm <sup>2</sup>	50 pair	0.5 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	18.0 mm	648 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-50PAIR-0P75MM2 50 pair 0.75 mm <sup>2</sup>	50 pair	0.75 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	18.2 mm	871 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-50PAIR-1P0MM2 50 pair 1.0 mm <sup>2</sup>	50 pair	1.0 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	120 pF/m guide	40 uH/ohm	18.3 mm	1093 kg/km
UEC-EN50288-7-PVC-PVC-CWB-MULTIPAIR-50PAIR-1P5MM2 50 pair 1.5 mm <sup>2</sup>	50 pair	1.5 mm <sup>2</sup>	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	120 pF/m guide	40 uH/ohm	18.6 mm	1538 kg/km