



COPPER WIRE BRAID SCREENED

EN 50288-7

4 orderable sizes

STANDARD EN 50288-7	VOLTAGE CLASS 300/500 V or 500 V application reference	CONDUCTOR 0.5 mm ² , 0.75 mm ² , 1.0 mm ² , 1.5 mm ² and customer- specified sizes
INSULATION / JACKET PVC	CROSS-SECTION RANGE 1 pair	

Construction

- 1 ■ **Conductor (per core)** – Bare or tinned annealed copper conductor · 1 × Ø1.13 mm · IEC 60228 cl.1
- 2 ■ **Pair insulation** – PVC
- 3 ■ **Filler** – Bedding / filler
- 4 ■ **Overall screen (OS)** – Al/polyester foil + drain
- 5 ■ **Sheath** – PVC

Size selection — all available cross-sections

Cable reference	Pair / triple / core layout	Conductor size	Conductor class	Max DC resistance at 20 °C	Mutual capacitance	L/R ratio	OD guide	Weight guide
UEC-EN50288-7-PVC-PVC-CWB-SINGLE-PAIR-1PAIR-ØP5MM2 1 pair 0.5 mm ²	1 pair	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	115 pF/m guide	25 uH/ohm	8.2 mm	89 kg/km
UEC-EN50288-7-PVC-PVC-CWB-SINGLE-PAIR-1PAIR-ØP75MM2 1 pair 0.75 mm ²	1 pair	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	115 pF/m guide	25 uH/ohm	8.3 mm	94 kg/km
UEC-EN50288-7-PVC-PVC-CWB-SINGLE-PAIR-1PAIR-1PØMM2 1 pair 1.0 mm ²	1 pair	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	115 pF/m guide	40 uH/ohm	8.5 mm	98 kg/km

Cable reference	Pair / triple / core layout	Conductor size	Conductor class	Max DC resistance at 20 °C	Mutual capacitance	L/R ratio	OD guide	Weight guide
UEC-EN50288-7-PVC-PVC-CWB-SINGLE-PAIR-1PAIR-1P5MM2 1 pair 1.5 mm ²	1 pair	1.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	115 pF/m guide	40 uH/ohm	8.7 mm	107 kg/km

UE Cable · China — sales@uecable.com · uecable.com Confirm colour, printing, packing length, delivery country and test documents on enquiry.