









INDIVIDUAL AND OVERALL SCREENED ARMoured

EN 50288-7

28 orderable sizes

STANDARD EN 50288-7	VOLTAGE CLASS 300/500 V or 500 V application reference	CONDUCTOR 0.5 mm², 0.75 mm², 1.0 mm², 1.5 mm² and customer- specified sizes
INSULATION / JACKET XLPE	CROSS-SECTION RANGE 2 triple to 24 triple available range	

Construction

- 1  **Conductor (per core)** – Bare or tinned annealed copper conductor · 1 × Ø1.13 mm · IEC 60228 cl.1 / 2 / 5
- 2  **Triad insulation** – XLPE
- 3  **Individual screen (IS)** – Al/polyester foil + tinned-copper drain
- 4  **Filler** – Bedding / filler
- 5  **Overall screen (OS)** – Al/polyester foil + drain
- 6  **Bedding** – PVC bedding
- 7  **Armour** – Galvanised steel wire armour (SWA)
- 8  **Sheath** – LSZH

Size selection – all available cross-sections

Cable reference	Pair / triple / core layout	Conductor size	Conductor class	Max DC resistance at 20 °C	Mutual capacitance	L/R ratio	OD guide	Weight guide
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPLE-2TRIPLE-ØP5MM2 2 triple 0.5 mm ²	2 triple	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	75 pF/m guide	25 uH/ohm	12.6 mm	248 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPLE-2TRIPLE-ØP75MM2 2 triple 0.75 mm ²	2 triple	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	75 pF/m guide	25 uH/ohm	12.9 mm	261 kg/km

Cable reference	Pair / triple / core layout	Conductor size	Conductor class	Max DC resistance at 20 °C	Mutual capacitance	L/R ratio	OD guide	Weight guide
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPL-2TRIPLE-1P0MM2 2 triple 1.0 mm ²	2 triple	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	85 pF/m guide	40 uH/ohm	13.0 mm	275 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPL-2TRIPLE-1P5MM2 2 triple 1.5 mm ²	2 triple	1.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	85 pF/m guide	40 uH/ohm	13.3 mm	302 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPL-4TRIPLE-0P5MM2 4 triple 0.5 mm ²	4 triple	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	75 pF/m guide	25 uH/ohm	13.5 mm	285 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPL-4TRIPLE-0P75MM2 4 triple 0.75 mm ²	4 triple	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	75 pF/m guide	25 uH/ohm	13.7 mm	312 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPL-4TRIPLE-1P0MM2 4 triple 1.0 mm ²	4 triple	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	85 pF/m guide	40 uH/ohm	13.9 mm	339 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPL-4TRIPLE-1P5MM2 4 triple 1.5 mm ²	4 triple	1.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	85 pF/m guide	40 uH/ohm	14.2 mm	392 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPL-8TRIPLE-0P5MM2 8 triple 0.5 mm ²	8 triple	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	75 pF/m guide	25 uH/ohm	14.7 mm	359 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPL-8TRIPLE-0P75MM2 8 triple 0.75 mm ²	8 triple	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	75 pF/m guide	25 uH/ohm	15.0 mm	413 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPL-8TRIPLE-1P0MM2 8 triple 1.0 mm ²	8 triple	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	85 pF/m guide	40 uH/ohm	15.1 mm	466 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPL-8TRIPLE-	8 triple	1.5 mm ²	Class 1 (solid) / 2 (stranded)	13.43 Ω/km	85 pF/m guide	40 uH/ohm	15.4 mm	573 kg/km

Cable reference	Pair / triple / core layout	Conductor size	Conductor class	Max DC resistance at 20 °C	Mutual capacitance	L/R ratio	OD guide	Weight guide
1P5MM2 8 triple 1.5 mm ²			/ 5 (flexible)					
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIIPLE-12TRIIPLE-0P5MM2 12 triple 0.5 mm ²	12 triple	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	75 pF/m guide	25 uH/ohm	15.7 mm	434 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIIPLE-12TRIIPLE-0P75MM2 12 triple 0.75 mm ²	12 triple	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	75 pF/m guide	25 uH/ohm	15.9 mm	514 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIIPLE-12TRIIPLE-1P0MM2 12 triple 1.0 mm ²	12 triple	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	85 pF/m guide	40 uH/ohm	16.1 mm	594 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIIPLE-12TRIIPLE-1P5MM2 12 triple 1.5 mm ²	12 triple	1.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	85 pF/m guide	40 uH/ohm	16.4 mm	754 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIIPLE-16TRIIPLE-0P5MM2 16 triple 0.5 mm ²	16 triple	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	75 pF/m guide	25 uH/ohm	16.5 mm	508 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIIPLE-16TRIIPLE-0P75MM2 16 triple 0.75 mm ²	16 triple	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	75 pF/m guide	25 uH/ohm	16.7 mm	615 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIIPLE-16TRIIPLE-1P0MM2 16 triple 1.0 mm ²	16 triple	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	85 pF/m guide	40 uH/ohm	16.9 mm	721 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIIPLE-16TRIIPLE-1P5MM2 16 triple 1.5 mm ²	16 triple	1.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	85 pF/m guide	40 uH/ohm	17.2 mm	935 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIIPLE-20TRIIPLE-0P5MM2 20 triple 0.5 mm ²	20 triple	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	75 pF/m guide	25 uH/ohm	17.2 mm	582 kg/km

Cable reference	Pair / triple / core layout	Conductor size	Conductor class	Max DC resistance at 20 °C	Mutual capacitance	L/R ratio	OD guide	Weight guide
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPLER-20TRIPLE-0P75MM2 20 triple 0.75 mm ²	20 triple	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	75 pF/m guide	25 uH/ohm	17.4 mm	716 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPLER-20TRIPLE-1P0MM2 20 triple 1.0 mm ²	20 triple	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	85 pF/m guide	40 uH/ohm	17.6 mm	849 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPLER-20TRIPLE-1P5MM2 20 triple 1.5 mm ²	20 triple	1.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	85 pF/m guide	40 uH/ohm	17.9 mm	1116 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPLER-24TRIPLE-0P5MM2 24 triple 0.5 mm ²	24 triple	0.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	39.39 Ω/km	75 pF/m guide	25 uH/ohm	17.8 mm	656 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPLER-24TRIPLE-0P75MM2 24 triple 0.75 mm ²	24 triple	0.75 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	26.8 Ω/km	75 pF/m guide	25 uH/ohm	18.0 mm	816 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPLER-24TRIPLE-1P0MM2 24 triple 1.0 mm ²	24 triple	1.0 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	19.7 Ω/km	85 pF/m guide	40 uH/ohm	18.2 mm	977 kg/km
UEC-EN50288-7-XLPE-LSZH-IOS-SWA-MULTITRIPLER-24TRIPLE-1P5MM2 24 triple 1.5 mm ²	24 triple	1.5 mm ²	Class 1 (solid) / 2 (stranded) / 5 (flexible)	13.43 Ω/km	85 pF/m guide	40 uH/ohm	18.5 mm	1297 kg/km