



## EUROPEAN LOW SMOKE POWER CABLE

VDE 0276

63 orderable sizes

STANDARD <b>VDE 0276</b>	VOLTAGE CLASS <b>0.6/1 kV</b>	CONDUCTOR <b>Copper conductor</b>
INSULATION / JACKET <b>LSZH</b>		

### Construction

- 1 ■ Conductor (per core) – Copper conductor · 7 × Ø2.13 mm · IEC 60228 cl.2
- 2 ■ Core insulation – XLPE
- 3 ■ Filler – PP filler
- 4 ■ Sheath – LSZH

### Size selection — all available cross-sections

Cable reference	Core layout	Conductor size	Conductor	Max DC resistance at 20 °C	OD guide
N2XH 1C Copper 16 mm <sup>2</sup> LSZH	1C	16 mm <sup>2</sup>	Copper conductor	1.15 Ω/km	19 mm
N2XH 1C Copper 25 mm <sup>2</sup> LSZH	1C	25 mm <sup>2</sup>	Copper conductor	0.727 Ω/km	21 mm
N2XH 1C Copper 50 mm <sup>2</sup> LSZH	1C	50 mm <sup>2</sup>	Copper conductor	0.387 Ω/km	26 mm
N2XH 1C Copper 70 mm <sup>2</sup> LSZH	1C	70 mm <sup>2</sup>	Copper conductor	0.268 Ω/km	29 mm
N2XH 1C Copper 95 mm <sup>2</sup> LSZH	1C	95 mm <sup>2</sup>	Copper conductor	0.193 Ω/km	32 mm
N2XH 1C Copper 150 mm <sup>2</sup> LSZH	1C	150 mm <sup>2</sup>	Copper conductor	0.124 Ω/km	37 mm
N2XH 1C Copper 240 mm <sup>2</sup> LSZH	1C	240 mm <sup>2</sup>	Copper conductor	0.0754 Ω/km	44 mm
N2XH 1C Copper 400 mm <sup>2</sup> LSZH	1C	400 mm <sup>2</sup>	Copper conductor	0.0470 Ω/km	54 mm
N2XH 2C Copper 1.5 mm <sup>2</sup> LSZH	2C	1.5 mm <sup>2</sup>	Copper conductor	12.1 Ω/km	15 mm

Cable reference	Core layout	Conductor size	Conductor	Max DC resistance at 20 °C	OD guide
N2XH 2C Copper 2.5 mm <sup>2</sup> LSZH	2C	2.5 mm <sup>2</sup>	Copper conductor	7.41 Ω/km	16 mm
N2XH 2C Copper 4 mm <sup>2</sup> LSZH	2C	4 mm <sup>2</sup>	Copper conductor	4.61 Ω/km	17 mm
N2XH 2C Copper 6 mm <sup>2</sup> LSZH	2C	6 mm <sup>2</sup>	Copper conductor	3.08 Ω/km	18 mm
N2XH 2C Copper 10 mm <sup>2</sup> LSZH	2C	10 mm <sup>2</sup>	Copper conductor	1.83 Ω/km	20 mm
N2XH 2C Copper 16 mm <sup>2</sup> LSZH	2C	16 mm <sup>2</sup>	Copper conductor	1.15 Ω/km	21 mm
N2XH 2C Copper 25 mm <sup>2</sup> LSZH	2C	25 mm <sup>2</sup>	Copper conductor	0.727 Ω/km	24 mm
N2XH 2C Copper 35 mm <sup>2</sup> LSZH	2C	35 mm <sup>2</sup>	Copper conductor	0.524 Ω/km	26 mm
N2XH 2C Copper 50 mm <sup>2</sup> LSZH	2C	50 mm <sup>2</sup>	Copper conductor	0.387 Ω/km	28 mm
N2XH 2C Copper 70 mm <sup>2</sup> LSZH	2C	70 mm <sup>2</sup>	Copper conductor	0.268 Ω/km	31 mm
N2XH 2C Copper 95 mm <sup>2</sup> LSZH	2C	95 mm <sup>2</sup>	Copper conductor	0.193 Ω/km	34 mm
N2XH 2C Copper 120 mm <sup>2</sup> LSZH	2C	120 mm <sup>2</sup>	Copper conductor	0.153 Ω/km	37 mm
N2XH 2C Copper 150 mm <sup>2</sup> LSZH	2C	150 mm <sup>2</sup>	Copper conductor	0.124 Ω/km	40 mm
N2XH 2C Copper 185 mm <sup>2</sup> LSZH	2C	185 mm <sup>2</sup>	Copper conductor	0.0991 Ω/km	43 mm
N2XH 2C Copper 240 mm <sup>2</sup> LSZH	2C	240 mm <sup>2</sup>	Copper conductor	0.0754 Ω/km	47 mm
N2XH 3C Copper 1.5 mm <sup>2</sup> LSZH	3C	1.5 mm <sup>2</sup>	Copper conductor	12.1 Ω/km	18 mm
N2XH 3C Copper 2.5 mm <sup>2</sup> LSZH	3C	2.5 mm <sup>2</sup>	Copper conductor	7.41 Ω/km	18 mm
N2XH 3C Copper 4 mm <sup>2</sup> LSZH	3C	4 mm <sup>2</sup>	Copper conductor	4.61 Ω/km	19 mm
N2XH 3C Copper 6 mm <sup>2</sup> LSZH	3C	6 mm <sup>2</sup>	Copper conductor	3.08 Ω/km	20 mm
N2XH 3C Copper 10 mm <sup>2</sup> LSZH	3C	10 mm <sup>2</sup>	Copper conductor	1.83 Ω/km	22 mm
N2XH 3C Copper 16 mm <sup>2</sup> LSZH	3C	16 mm <sup>2</sup>	Copper conductor	1.15 Ω/km	24 mm
N2XH 3C Copper 25 mm <sup>2</sup> LSZH	3C	25 mm <sup>2</sup>	Copper conductor	0.727 Ω/km	26 mm

Cable reference	Core layout	Conductor size	Conductor	Max DC resistance at 20 °C	OD guide
N2XH 3C Copper 35 mm <sup>2</sup> LSZH	3C	35 mm <sup>2</sup>	Copper conductor	0.524 Ω/km	28 mm
N2XH 3C Copper 50 mm <sup>2</sup> LSZH	3C	50 mm <sup>2</sup>	Copper conductor	0.387 Ω/km	30 mm
N2XH 3C Copper 70 mm <sup>2</sup> LSZH	3C	70 mm <sup>2</sup>	Copper conductor	0.268 Ω/km	33 mm
N2XH 3C Copper 95 mm <sup>2</sup> LSZH	3C	95 mm <sup>2</sup>	Copper conductor	0.193 Ω/km	36 mm
N2XH 3C Copper 120 mm <sup>2</sup> LSZH	3C	120 mm <sup>2</sup>	Copper conductor	0.153 Ω/km	39 mm
N2XH 3C Copper 150 mm <sup>2</sup> LSZH	3C	150 mm <sup>2</sup>	Copper conductor	0.124 Ω/km	42 mm
N2XH 3C Copper 185 mm <sup>2</sup> LSZH	3C	185 mm <sup>2</sup>	Copper conductor	0.0991 Ω/km	45 mm
N2XH 3C Copper 240 mm <sup>2</sup> LSZH	3C	240 mm <sup>2</sup>	Copper conductor	0.0754 Ω/km	49 mm
N2XH 4C Copper 1.5 mm <sup>2</sup> LSZH	4C	1.5 mm <sup>2</sup>	Copper conductor	12.1 Ω/km	20 mm
N2XH 4C Copper 2.5 mm <sup>2</sup> LSZH	4C	2.5 mm <sup>2</sup>	Copper conductor	7.41 Ω/km	21 mm
N2XH 4C Copper 4 mm <sup>2</sup> LSZH	4C	4 mm <sup>2</sup>	Copper conductor	4.61 Ω/km	22 mm
N2XH 4C Copper 6 mm <sup>2</sup> LSZH	4C	6 mm <sup>2</sup>	Copper conductor	3.08 Ω/km	23 mm
N2XH 4C Copper 10 mm <sup>2</sup> LSZH	4C	10 mm <sup>2</sup>	Copper conductor	1.83 Ω/km	24 mm
N2XH 4C Copper 16 mm <sup>2</sup> LSZH	4C	16 mm <sup>2</sup>	Copper conductor	1.15 Ω/km	26 mm
N2XH 4C Copper 25 mm <sup>2</sup> LSZH	4C	25 mm <sup>2</sup>	Copper conductor	0.727 Ω/km	28 mm
N2XH 4C Copper 35 mm <sup>2</sup> LSZH	4C	35 mm <sup>2</sup>	Copper conductor	0.524 Ω/km	30 mm
N2XH 4C Copper 50 mm <sup>2</sup> LSZH	4C	50 mm <sup>2</sup>	Copper conductor	0.387 Ω/km	33 mm
N2XH 4C Copper 70 mm <sup>2</sup> LSZH	4C	70 mm <sup>2</sup>	Copper conductor	0.268 Ω/km	36 mm
N2XH 4C Copper 95 mm <sup>2</sup> LSZH	4C	95 mm <sup>2</sup>	Copper conductor	0.193 Ω/km	39 mm
N2XH 4C Copper 120 mm <sup>2</sup> LSZH	4C	120 mm <sup>2</sup>	Copper conductor	0.153 Ω/km	41 mm
N2XH 4C Copper 150 mm <sup>2</sup> LSZH	4C	150 mm <sup>2</sup>	Copper conductor	0.124 Ω/km	44 mm

Cable reference	Core layout	Conductor size	Conductor	Max DC resistance at 20 °C	OD guide
N2XH 4C Copper 185 mm <sup>2</sup> LSZH	4C	185 mm <sup>2</sup>	Copper conductor	0.0991 Ω/km	47 mm
N2XH 4C Copper 240 mm <sup>2</sup> LSZH	4C	240 mm <sup>2</sup>	Copper conductor	0.0754 Ω/km	51 mm
N2XH 5C Copper 1.5 mm <sup>2</sup> LSZH	5C	1.5 mm <sup>2</sup>	Copper conductor	12.1 Ω/km	22 mm
N2XH 5C Copper 2.5 mm <sup>2</sup> LSZH	5C	2.5 mm <sup>2</sup>	Copper conductor	7.41 Ω/km	23 mm
N2XH 5C Copper 4 mm <sup>2</sup> LSZH	5C	4 mm <sup>2</sup>	Copper conductor	4.61 Ω/km	24 mm
N2XH 5C Copper 6 mm <sup>2</sup> LSZH	5C	6 mm <sup>2</sup>	Copper conductor	3.08 Ω/km	25 mm
N2XH 5C Copper 10 mm <sup>2</sup> LSZH	5C	10 mm <sup>2</sup>	Copper conductor	1.83 Ω/km	26 mm
N2XH 5C Copper 16 mm <sup>2</sup> LSZH	5C	16 mm <sup>2</sup>	Copper conductor	1.15 Ω/km	28 mm
N2XH 5C Copper 25 mm <sup>2</sup> LSZH	5C	25 mm <sup>2</sup>	Copper conductor	0.727 Ω/km	31 mm
N2XH 5C Copper 35 mm <sup>2</sup> LSZH	5C	35 mm <sup>2</sup>	Copper conductor	0.524 Ω/km	33 mm
N2XH 5C Copper 50 mm <sup>2</sup> LSZH	5C	50 mm <sup>2</sup>	Copper conductor	0.387 Ω/km	35 mm
N2XH 5C Copper 70 mm <sup>2</sup> LSZH	5C	70 mm <sup>2</sup>	Copper conductor	0.268 Ω/km	38 mm