



OFFSHORE REELING CABLE

DIN VDE 0250

21 orderable sizes

STANDARD DIN VDE 0250	VOLTAGE CLASS 0.6/1 kV	CONDUCTOR Flexible copper conductor
INSULATION / JACKET Offshore PUR mud and oil resistant sheath		

Construction

- 1 ■ Conductor (per core) – Flexible copper conductor · 196 × Ø0.4 mm · IEC 60228 c1.5
- 2 ■ Core insulation – Special polymer power-core insulation
- 3 ■ Filler – PP filler
- 4 ■ Sheath – Offshore PUR mud and oil resistant sheath

Size selection — all available cross-sections

Cable reference	Reel duty	Reel system	Core / element design	Conductor size	Max DC resistance at 20 °C	OD guide	Tensile support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 4G 2.5 mm ²	Offshore spring and motor reel duty	Offshore cable reel	4G	2.5 mm ²	7.6 Ω/km	20.6 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 4G 4 mm ²	Offshore spring and motor reel duty	Offshore cable reel	4G	4 mm ²	4.7 Ω/km	21.4 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 4G 6 mm ²	Offshore spring and motor reel duty	Offshore cable reel	4G	6 mm ²	3.1 Ω/km	22.3 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 4G 10 mm ²	Offshore spring and motor reel duty	Offshore cable reel	4G	10 mm ²	1.83 Ω/km	23.7 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 4G 16 mm ²	Offshore spring and motor reel duty	Offshore cable reel	4G	16 mm ²	1.15 Ω/km	25.4 mm	Aramid yarn reinforced support

Cable reference	Reel duty	Reel system	Core / element design	Conductor size	Max DC resistance at 20 °C	OD guide	Tensile support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 4G 25 mm ²	Offshore spring and motor reel duty	Offshore cable reel	4G	25 mm ²	0.727 Ω/km	27.4 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 4G 35 mm ²	Offshore spring and motor reel duty	Offshore cable reel	4G	35 mm ²	0.524 Ω/km	29.2 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 5G 2.5 mm ²	Offshore spring and motor reel duty	Offshore cable reel	5G	2.5 mm ²	7.6 Ω/km	21.1 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 5G 4 mm ²	Offshore spring and motor reel duty	Offshore cable reel	5G	4 mm ²	4.7 Ω/km	21.9 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 5G 6 mm ²	Offshore spring and motor reel duty	Offshore cable reel	5G	6 mm ²	3.1 Ω/km	22.8 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 5G 10 mm ²	Offshore spring and motor reel duty	Offshore cable reel	5G	10 mm ²	1.83 Ω/km	24.2 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 5G 16 mm ²	Offshore spring and motor reel duty	Offshore cable reel	5G	16 mm ²	1.15 Ω/km	25.9 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 5G 25 mm ²	Offshore spring and motor reel duty	Offshore cable reel	5G	25 mm ²	0.727 Ω/km	27.9 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 5G 35 mm ²	Offshore spring and motor reel duty	Offshore cable reel	5G	35 mm ²	0.524 Ω/km	29.8 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 7G 2.5 mm ²	Offshore spring and motor reel duty	Offshore cable reel	7G	2.5 mm ²	7.6 Ω/km	22.0 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 7G 4 mm ²	Offshore spring and motor reel duty	Offshore cable reel	7G	4 mm ²	4.7 Ω/km	22.8 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 7G 6 mm ²	Offshore spring and motor reel duty	Offshore cable reel	7G	6 mm ²	3.1 Ω/km	23.7 mm	Aramid yarn reinforced support

Cable reference	Reel duty	Reel system	Core / element design	Conductor size	Max DC resistance at 20 °C	OD guide	Tensile support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 7G 10 mm ²	Offshore spring and motor reel duty	Offshore cable reel	7G	10 mm ²	1.83 Ω/km	25.1 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 7G 16 mm ²	Offshore spring and motor reel duty	Offshore cable reel	7G	16 mm ²	1.15 Ω/km	26.8 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 7G 25 mm ²	Offshore spring and motor reel duty	Offshore cable reel	7G	25 mm ²	0.727 Ω/km	28.8 mm	Aramid yarn reinforced support
Offshore PUR reeling cable 0.6/1 kV Offshore cable reel 7G 35 mm ²	Offshore spring and motor reel duty	Offshore cable reel	7G	35 mm ²	0.524 Ω/km	30.7 mm	Aramid yarn reinforced support

UE Cable · China — sales@uecable.com · uecable.com Confirm colour, printing, packing length, delivery country and test documents on enquiry.