



PTFE INSULATED EQUIPMENT WIRE

UL 758 / IEC 60228 reference

9 orderable sizes

STANDARD UL 758 / IEC 60228 reference	VOLTAGE CLASS 300/500 V or 600 V	TEMPERATURE CLASS -60 °C to +200 °C or +260 °C by grade
CONDUCTOR Silver-plated or nickel-plated copper conductor	INSULATION / JACKET PTFE fluoropolymer finish	

Construction

- 1 ■ **Conductor** – Silver-plated or nickel-plated copper conductor · 7 × Ø0.52 mm · IEC 60228 cl.2
- 2 ■ **Insulation** – PTFE fluoropolymer insulation

Size selection — all available cross-sections

Cable reference	Heat duty	Core design	Conductor size	Voltage class	Max DC resistance at 20 °C	OD guide	Cable weight
PTFE hook-up wire 300/500 V or 600 V Chemical and high-temperature equipment wiring 1 core 0.25 mm ²	Chemical and high-temperature equipment wiring	1 core	0.25 mm ²	300/500 V or 600 V	74.0 Ω/km	3.4 mm	0.13 kg/m
PTFE hook-up wire 300/500 V or 600 V Chemical and high-temperature equipment wiring 1 core 0.5 mm ²	Chemical and high-temperature equipment wiring	1 core	0.5 mm ²	300/500 V or 600 V	37.1 Ω/km	3.7 mm	0.14 kg/m
PTFE hook-up wire 300/500 V or 600 V Chemical and high-temperature equipment wiring 1 core 0.75 mm ²	Chemical and high-temperature equipment wiring	1 core	0.75 mm ²	300/500 V or 600 V	24.7 Ω/km	3.9 mm	0.14 kg/m
PTFE hook-up wire 300/500 V or 600 V Chemical and high-temperature equipment wiring 1 core 1.0 mm ²	Chemical and high-temperature equipment wiring	1 core	1.0 mm ²	300/500 V or 600 V	18.5 Ω/km	4.1 mm	0.14 kg/m
PTFE hook-up wire 300/500 V or 600 V	Chemical and high-temperature	1 core	1.5 mm ²	300/500 V or 600 V	12.7 Ω/km	4.4 mm	0.15 kg/m

Cable reference	Heat duty	Core design	Conductor size	Voltage class	Max DC resistance at 20 °C	OD guide	Cable weight
Chemical and high-temperature equipment wiring 1 core 1.5 mm ²	equipment wiring			V			
PTFE hook-up wire 300/500 V or 600 V Chemical and high-temperature equipment wiring 1 core 2.5 mm ²	Chemical and high-temperature equipment wiring	1 core	2.5 mm ²	300/500 V or 600 V	7.6 Ω/km	4.8 mm	0.16 kg/m
PTFE hook-up wire 300/500 V or 600 V Chemical and high-temperature equipment wiring 1 core 4 mm ²	Chemical and high-temperature equipment wiring	1 core	4 mm ²	300/500 V or 600 V	4.7 Ω/km	5.4 mm	0.17 kg/m
PTFE hook-up wire 300/500 V or 600 V Chemical and high-temperature equipment wiring 1 core 6 mm ²	Chemical and high-temperature equipment wiring	1 core	6 mm ²	300/500 V or 600 V	3.1 Ω/km	6.0 mm	0.20 kg/m
PTFE hook-up wire 300/500 V or 600 V Chemical and high-temperature equipment wiring 1 core 10 mm ²	Chemical and high-temperature equipment wiring	1 core	10 mm ²	300/500 V or 600 V	1.83 Ω/km	7.0 mm	0.24 kg/m

UE Cable · China — sales@uecable.com · uecable.com Confirm colour, printing, packing length, delivery country and test documents on enquiry.