



**LARGE DIAMETER RF COAXIAL CABLE**

MIL-C-17 / RG type references

2 orderable sizes

<b>STANDARD</b> MIL-C-17 / RG type references	<b>CONDUCTOR</b> Stranded bare copper conductor	<b>INSULATION / JACKET</b> PVC, LSZH or PE outdoor jacket
--------------------------------------------------	----------------------------------------------------	--------------------------------------------------------------

**Construction**

- 1 ■ Centre conductor – Stranded bare copper conductor
- 2 ■ Dielectric – Solid PE dielectric
- 3 ■ Foil screen – Aluminium/polyester foil
- 4 ■ Braid screen – Braid shield (C)
- 5 ■ Sheath – PVC, LSZH or PE outdoor jacket

**Size selection — all available cross-sections**

Cable reference	Application	Coax reference	Impedance	Center conductor	Dielectric	Shield construction	Jacket	OD guide	Electrical reference
<b>RG213 PE outdoor Coaxial Cable</b>	RF feeder, base station and antenna route	RG213	50 Ω	Stranded bare copper conductor	Solid PE dielectric	Bare copper braid screen	PE outdoor jacket	10.30 mm	101 pF/m nominal; 0.28 dB/m at 400 MHz guide; 66% nominal velocity factor
<b>RG213 Direct burial PE Coaxial Cable</b>	RF feeder, base station and antenna route	RG213	50 Ω	Stranded bare copper conductor	Solid PE dielectric	Bare copper braid screen	Direct burial PE jacket	10.30 mm	101 pF/m nominal; 0.28 dB/m at 400 MHz guide; 66% nominal velocity factor