



WATER-BLOCKED ALUMINIUM MV CABLE

IEC 60502-2

24 orderable sizes

STANDARD IEC 60502-2	VOLTAGE CLASS 3.6/6 kV to 18/30 kV and customer-specified MV classes	CONDUCTOR Aluminium conductor
INSULATION / JACKET LSZH polyolefin		

Construction

- 1 **Conductor** – Aluminium conductor · 37 × Ø2.03 mm · IEC 60228 cl.2
- 2 **Conductor screen** – Semi-conducting layer
- 3 **Insulation** – XLPE
- 4 **Insulation screen** – Semi-conducting layer
- 5 **Metallic screen** – Copper wire screen (CWS)
- 6 **Sheath** – LSZH polyolefin

Size selection — all available cross-sections

Cable reference	Voltage class	Cross-section	Max DC resistance at 20 °C	Metallic screen	OD guide
RHZ1 AL 0L 20L 6/10 kV Single core Aluminium 35 mm ² LSZH polyolefin	6/10 kV	35 mm ²	0.868 Ω/km	16 mm ² copper wire screen	32 mm
RHZ1 AL 0L 20L 6/10 kV Single core Aluminium 70 mm ² LSZH polyolefin	6/10 kV	70 mm ²	0.443 Ω/km	16 mm ² copper wire screen	36 mm
RHZ1 AL 0L 20L 6/10 kV Single core Aluminium 120 mm ² LSZH polyolefin	6/10 kV	120 mm ²	0.253 Ω/km	16 mm ² copper wire screen	41 mm
RHZ1 AL 0L 20L 6/10 kV Single core Aluminium 185 mm ² LSZH polyolefin	6/10 kV	185 mm ²	0.164 Ω/km	25 mm ² copper wire screen	45 mm
RHZ1 AL 0L 20L 6/10 kV Single core Aluminium 300 mm ² LSZH polyolefin	6/10 kV	300 mm ²	0.100 Ω/km	25 mm ² copper wire screen	51 mm

Cable reference	Voltage class	Cross-section	Max DC resistance at 20 °C	Metallic screen	OD guide
RHZ1 AL OL 20L 6/10 kV Single core Aluminium 500 mm ² LSZH polyolefin	6/10 kV	500 mm ²	0.0605 Ω/km	35 mm ² copper wire screen	60 mm
RHZ1 AL OL 20L 12/20 kV Single core Aluminium 50 mm ² LSZH polyolefin	12/20 kV	50 mm ²	0.641 Ω/km	16 mm ² copper wire screen	37 mm
RHZ1 AL OL 20L 12/20 kV Single core Aluminium 95 mm ² LSZH polyolefin	12/20 kV	95 mm ²	0.320 Ω/km	16 mm ² copper wire screen	42 mm
RHZ1 AL OL 20L 12/20 kV Single core Aluminium 150 mm ² LSZH polyolefin	12/20 kV	150 mm ²	0.206 Ω/km	16 mm ² copper wire screen	46 mm
RHZ1 AL OL 20L 12/20 kV Single core Aluminium 240 mm ² LSZH polyolefin	12/20 kV	240 mm ²	0.125 Ω/km	25 mm ² copper wire screen	51 mm
RHZ1 AL OL 20L 12/20 kV Single core Aluminium 400 mm ² LSZH polyolefin	12/20 kV	400 mm ²	0.0778 Ω/km	35 mm ² copper wire screen	59 mm
RHZ1 AL OL 20L 12/20 kV Single core Aluminium 630 mm ² LSZH polyolefin	12/20 kV	630 mm ²	0.0469 Ω/km	35 mm ² copper wire screen	68 mm
RHZ1 AL OL 20L 18/30 kV Single core Aluminium 70 mm ² LSZH polyolefin	18/30 kV	70 mm ²	0.443 Ω/km	16 mm ² copper wire screen	42 mm
RHZ1 AL OL 20L 18/30 kV Single core Aluminium 120 mm ² LSZH polyolefin	18/30 kV	120 mm ²	0.253 Ω/km	16 mm ² copper wire screen	47 mm
RHZ1 AL OL 20L 18/30 kV Single core Aluminium 185 mm ² LSZH polyolefin	18/30 kV	185 mm ²	0.164 Ω/km	25 mm ² copper wire screen	51 mm
RHZ1 AL OL 20L 18/30 kV Single core Aluminium 300 mm ² LSZH polyolefin	18/30 kV	300 mm ²	0.100 Ω/km	25 mm ² copper wire screen	57 mm
RHZ1 AL OL 20L 18/30 kV Single core Aluminium 500 mm ² LSZH polyolefin	18/30 kV	500 mm ²	0.0605 Ω/km	35 mm ² copper wire screen	66 mm
RHZ1 AL OL 20L 18/30 kV Single core Aluminium 630 mm ² LSZH polyolefin	18/30 kV	630 mm ²	0.0469 Ω/km	35 mm ² copper wire screen	71 mm
RHZ1 AL OL 20L Project voltage Single core Aluminium 50 mm ² LSZH polyolefin	Project voltage	50 mm ²	0.641 Ω/km	16 mm ² copper wire screen	34 mm
RHZ1 AL OL 20L Project voltage Single core Aluminium 95 mm ² LSZH polyolefin	Project voltage	95 mm ²	0.320 Ω/km	16 mm ² copper wire screen	39 mm

Cable reference	Voltage class	Cross-section	Max DC resistance at 20 °C	Metallic screen	OD guide
RHZ1 AL 0L 20L Project voltage Single core Aluminium 150 mm ² LSZH polyolefin	Project voltage	150 mm ²	0.206 Ω/km	16 mm ² copper wire screen	43 mm
RHZ1 AL 0L 20L Project voltage Single core Aluminium 240 mm ² LSZH polyolefin	Project voltage	240 mm ²	0.125 Ω/km	25 mm ² copper wire screen	48 mm
RHZ1 AL 0L 20L Project voltage Single core Aluminium 400 mm ² LSZH polyolefin	Project voltage	400 mm ²	0.0778 Ω/km	35 mm ² copper wire screen	56 mm
RHZ1 AL 0L 20L Project voltage Single core Aluminium 630 mm ² LSZH polyolefin	Project voltage	630 mm ²	0.0469 Ω/km	35 mm ² copper wire screen	65 mm

UE Cable · China — sales@uecable.com · uecable.com Confirm colour, printing, packing length, delivery country and test documents on enquiry.