



SCREENED SILICONE CONTROL CABLE

VDE / IEC silicone control cable reference

30 orderable sizes

STANDARD VDE / IEC silicone control cable reference	VOLTAGE CLASS 300/500 V	TEMPERATURE CLASS -60 °C to +180 °C flexible control service
CONDUCTOR Class 5 tinned copper conductor	INSULATION / JACKET Silicone rubber outer sheath	

Construction

- 1 ■ Conductor (per core) – Class 5 tinned copper conductor · 16 × Ø0.2 mm · IEC 60228 cl.5
- 2 ■ Core insulation – Silicone rubber core insulation
- 3 ■ Filler – PP filler
- 4 ■ Shield – Braid shield (C)
- 5 ■ Sheath – Silicone rubber outer sheath

Size selection — all available cross-sections

Cable reference	Heat duty	Core design	Conductor size	Voltage class	Max DC resistance at 20 °C	OD guide	Cable weight
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 2 core 0.5 mm ²	EMC-sensitive high-temperature control wiring	2 core	0.5 mm ²	300/500 V	37.1 Ω/km	9.4 mm	0.28 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 2 core 0.75 mm ²	EMC-sensitive high-temperature control wiring	2 core	0.75 mm ²	300/500 V	24.7 Ω/km	9.7 mm	0.29 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 2 core 1.0 mm ²	EMC-sensitive high-temperature control wiring	2 core	1.0 mm ²	300/500 V	18.5 Ω/km	9.9 mm	0.29 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 2 core 1.5 mm ²	EMC-sensitive high-temperature control wiring	2 core	1.5 mm ²	300/500 V	12.7 Ω/km	10.2 mm	0.30 kg/m

Cable reference	Heat duty	Core design	Conductor size	Voltage class	Max DC resistance at 20 °C	OD guide	Cable weight
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 2 core 2.5 mm ²	EMC-sensitive high-temperature control wiring	2 core	2.5 mm ²	300/500 V	7.6 Ω/km	10.7 mm	0.33 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 3 core 0.5 mm ²	EMC-sensitive high-temperature control wiring	3 core	0.5 mm ²	300/500 V	37.1 Ω/km	10.1 mm	0.29 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 3 core 0.75 mm ²	EMC-sensitive high-temperature control wiring	3 core	0.75 mm ²	300/500 V	24.7 Ω/km	10.3 mm	0.29 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 3 core 1.0 mm ²	EMC-sensitive high-temperature control wiring	3 core	1.0 mm ²	300/500 V	18.5 Ω/km	10.5 mm	0.30 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 3 core 1.5 mm ²	EMC-sensitive high-temperature control wiring	3 core	1.5 mm ²	300/500 V	12.7 Ω/km	10.9 mm	0.32 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 3 core 2.5 mm ²	EMC-sensitive high-temperature control wiring	3 core	2.5 mm ²	300/500 V	7.6 Ω/km	11.4 mm	0.35 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 4 core 0.5 mm ²	EMC-sensitive high-temperature control wiring	4 core	0.5 mm ²	300/500 V	37.1 Ω/km	10.7 mm	0.29 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 4 core 0.75 mm ²	EMC-sensitive high-temperature control wiring	4 core	0.75 mm ²	300/500 V	24.7 Ω/km	10.9 mm	0.30 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 4 core 1.0 mm ²	EMC-sensitive high-temperature control wiring	4 core	1.0 mm ²	300/500 V	18.5 Ω/km	11.1 mm	0.31 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 4 core 1.5 mm ²	EMC-sensitive high-temperature control wiring	4 core	1.5 mm ²	300/500 V	12.7 Ω/km	11.4 mm	0.34 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 4 core 2.5 mm ²	EMC-sensitive high-temperature control wiring	4 core	2.5 mm ²	300/500 V	7.6 Ω/km	12.0 mm	0.38 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 5 core 0.5 mm ²	EMC-sensitive high-temperature control wiring	5 core	0.5 mm ²	300/500 V	37.1 Ω/km	11.2 mm	0.30 kg/m

Cable reference	Heat duty	Core design	Conductor size	Voltage class	Max DC resistance at 20 °C	OD guide	Cable weight
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 5 core 0.75 mm ²	EMC-sensitive high-temperature control wiring	5 core	0.75 mm ²	300/500 V	24.7 Ω/km	11.4 mm	0.31 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 5 core 1.0 mm ²	EMC-sensitive high-temperature control wiring	5 core	1.0 mm ²	300/500 V	18.5 Ω/km	11.6 mm	0.33 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 5 core 1.5 mm ²	EMC-sensitive high-temperature control wiring	5 core	1.5 mm ²	300/500 V	12.7 Ω/km	11.9 mm	0.35 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 5 core 2.5 mm ²	EMC-sensitive high-temperature control wiring	5 core	2.5 mm ²	300/500 V	7.6 Ω/km	12.5 mm	0.41 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 7 core 0.5 mm ²	EMC-sensitive high-temperature control wiring	7 core	0.5 mm ²	300/500 V	37.1 Ω/km	12.0 mm	0.31 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 7 core 0.75 mm ²	EMC-sensitive high-temperature control wiring	7 core	0.75 mm ²	300/500 V	24.7 Ω/km	12.3 mm	0.33 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 7 core 1.0 mm ²	EMC-sensitive high-temperature control wiring	7 core	1.0 mm ²	300/500 V	18.5 Ω/km	12.5 mm	0.35 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 7 core 1.5 mm ²	EMC-sensitive high-temperature control wiring	7 core	1.5 mm ²	300/500 V	12.7 Ω/km	12.8 mm	0.39 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 7 core 2.5 mm ²	EMC-sensitive high-temperature control wiring	7 core	2.5 mm ²	300/500 V	7.6 Ω/km	13.3 mm	0.46 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 12 core 0.5 mm ²	EMC-sensitive high-temperature control wiring	12 core	0.5 mm ²	300/500 V	37.1 Ω/km	13.7 mm	0.34 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 12 core 0.75 mm ²	EMC-sensitive high-temperature control wiring	12 core	0.75 mm ²	300/500 V	24.7 Ω/km	14.0 mm	0.37 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 12 core 1.0 mm ²	EMC-sensitive high-temperature control wiring	12 core	1.0 mm ²	300/500 V	18.5 Ω/km	14.2 mm	0.40 kg/m

Cable reference	Heat duty	Core design	Conductor size	Voltage class	Max DC resistance at 20 °C	OD guide	Cable weight
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 12 core 1.5 mm ²	EMC-sensitive high-temperature control wiring	12 core	1.5 mm ²	300/500 V	12.7 Ω/km	14.5 mm	0.47 kg/m
SIHFC 300/500 V EMC-sensitive high-temperature control wiring 12 core 2.5 mm ²	EMC-sensitive high-temperature control wiring	12 core	2.5 mm ²	300/500 V	7.6 Ω/km	15.0 mm	0.60 kg/m

UE Cable · China — sales@uecable.com · uecable.com Confirm colour, printing, packing length, delivery country and test documents on enquiry.