



STA ARMoured POWER CABLE

IEC 60502-1

55 orderable sizes

STANDARD IEC 60502-1	VOLTAGE CLASS 0.6/1 kV	CONDUCTOR Copper or aluminium conductor
INSULATION / JACKET PVC outer sheath		

Construction

- 1 ■ Conductor (per core) – Copper conductor · 7 × Ø0.85 mm · IEC 60228 cl.2
- 2 ■ Core insulation – XLPE
- 3 ■ Filler – PP filler
- 4 ■ Shield – Foil shield (B)
- 5 ■ Bedding – PVC bedding
- 6 ■ Armour – Steel tape armour (STA)
- 7 ■ Sheath – PVC outer sheath

Size selection — all available cross-sections

Cable reference	Voltage class	Core layout	Cross-section	Conductor	Armour	Max DC resistance at 20 °C	OD guide	Weight guide
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 1.5 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	1.5 mm ²	Copper conductor	Steel tape armour	12.1 Ω/km	23 mm	0.71 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 2.5 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	2.5 mm ²	Copper conductor	Steel tape armour	7.41 Ω/km	24 mm	0.73 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 4 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	4 mm ²	Copper conductor	Steel tape armour	4.61 Ω/km	25 mm	0.77 kg/m

Cable reference	Voltage class	Core layout	Cross-section	Conductor	Armour	Max DC resistance at 20 °C	OD guide	Weight guide
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 6 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	6 mm ²	Copper conductor	Steel tape armour	3.08 Ω/km	26 mm	0.81 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 10 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	10 mm ²	Copper conductor	Steel tape armour	1.83 Ω/km	28 mm	0.90 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 16 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	16 mm ²	Copper conductor	Steel tape armour	1.15 Ω/km	29 mm	1.03 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 25 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	25 mm ²	Copper conductor	Steel tape armour	0.727 Ω/km	32 mm	1.23 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 35 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	35 mm ²	Copper conductor	Steel tape armour	0.524 Ω/km	34 mm	1.45 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 50 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	50 mm ²	Copper conductor	Steel tape armour	0.387 Ω/km	36 mm	1.78 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 70 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	70 mm ²	Copper conductor	Steel tape armour	0.268 Ω/km	39 mm	2.22 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 95 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	95 mm ²	Copper conductor	Steel tape armour	0.193 Ω/km	42 mm	2.77 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 120 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	120 mm ²	Copper conductor	Steel tape armour	0.153 Ω/km	45 mm	3.32 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 150 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	150 mm ²	Copper conductor	Steel tape armour	0.124 Ω/km	48 mm	3.98 kg/m

Cable reference	Voltage class	Core layout	Cross-section	Conductor	Armour	Max DC resistance at 20 °C	OD guide	Weight guide
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 185 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	185 mm ²	Copper conductor	Steel tape armour	0.0991 Ω/km	51 mm	4.75 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Copper 240 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	240 mm ²	Copper conductor	Steel tape armour	0.0754 Ω/km	55 mm	5.96 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 1.5 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	1.5 mm ²	Copper conductor	Steel tape armour	12.1 Ω/km	26 mm	0.73 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 2.5 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	2.5 mm ²	Copper conductor	Steel tape armour	7.41 Ω/km	26 mm	0.76 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 4 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	4 mm ²	Copper conductor	Steel tape armour	4.61 Ω/km	27 mm	0.81 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 6 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	6 mm ²	Copper conductor	Steel tape armour	3.08 Ω/km	28 mm	0.88 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 10 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	10 mm ²	Copper conductor	Steel tape armour	1.83 Ω/km	30 mm	1.01 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 16 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	16 mm ²	Copper conductor	Steel tape armour	1.15 Ω/km	32 mm	1.21 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 25 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	25 mm ²	Copper conductor	Steel tape armour	0.727 Ω/km	34 mm	1.50 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 35 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	35 mm ²	Copper conductor	Steel tape armour	0.524 Ω/km	36 mm	1.84 kg/m

Cable reference	Voltage class	Core layout	Cross-section	Conductor	Armour	Max DC resistance at 20 °C	OD guide	Weight guide
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 50 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	50 mm ²	Copper conductor	Steel tape armour	0.387 Ω/km	38 mm	2.33 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 70 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	70 mm ²	Copper conductor	Steel tape armour	0.268 Ω/km	41 mm	2.99 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 95 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	95 mm ²	Copper conductor	Steel tape armour	0.193 Ω/km	44 mm	3.81 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 120 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	120 mm ²	Copper conductor	Steel tape armour	0.153 Ω/km	47 mm	4.64 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 150 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	150 mm ²	Copper conductor	Steel tape armour	0.124 Ω/km	50 mm	5.63 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 185 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	185 mm ²	Copper conductor	Steel tape armour	0.0991 Ω/km	53 mm	6.78 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Copper 240 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	3C	240 mm ²	Copper conductor	Steel tape armour	0.0754 Ω/km	57 mm	8.60 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 1.5 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	1.5 mm ²	Copper conductor	Steel tape armour	12.1 Ω/km	28 mm	0.75 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 2.5 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	2.5 mm ²	Copper conductor	Steel tape armour	7.41 Ω/km	29 mm	0.79 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 4 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	4 mm ²	Copper conductor	Steel tape armour	4.61 Ω/km	30 mm	0.86 kg/m

Cable reference	Voltage class	Core layout	Cross-section	Conductor	Armour	Max DC resistance at 20 °C	OD guide	Weight guide
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 6 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	6 mm ²	Copper conductor	Steel tape armour	3.08 Ω/km	31 mm	0.94 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 10 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	10 mm ²	Copper conductor	Steel tape armour	1.83 Ω/km	32 mm	1.12 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 16 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	16 mm ²	Copper conductor	Steel tape armour	1.15 Ω/km	34 mm	1.38 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 25 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	25 mm ²	Copper conductor	Steel tape armour	0.727 Ω/km	36 mm	1.78 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 35 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	35 mm ²	Copper conductor	Steel tape armour	0.524 Ω/km	38 mm	2.22 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 50 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	50 mm ²	Copper conductor	Steel tape armour	0.387 Ω/km	41 mm	2.88 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 70 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	70 mm ²	Copper conductor	Steel tape armour	0.268 Ω/km	44 mm	3.76 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 95 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	95 mm ²	Copper conductor	Steel tape armour	0.193 Ω/km	47 mm	4.86 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 120 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	120 mm ²	Copper conductor	Steel tape armour	0.153 Ω/km	49 mm	5.96 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 150 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	150 mm ²	Copper conductor	Steel tape armour	0.124 Ω/km	52 mm	7.28 kg/m

Cable reference	Voltage class	Core layout	Cross-section	Conductor	Armour	Max DC resistance at 20 °C	OD guide	Weight guide
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 185 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	185 mm ²	Copper conductor	Steel tape armour	0.0991 Ω/km	55 mm	8.82 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Copper 240 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	4C	240 mm ²	Copper conductor	Steel tape armour	0.0754 Ω/km	59 mm	11.24 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Copper 1.5 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	5C	1.5 mm ²	Copper conductor	Steel tape armour	12.1 Ω/km	30 mm	0.76 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Copper 2.5 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	5C	2.5 mm ²	Copper conductor	Steel tape armour	7.41 Ω/km	31 mm	0.82 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Copper 4 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	5C	4 mm ²	Copper conductor	Steel tape armour	4.61 Ω/km	32 mm	0.90 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Copper 6 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	5C	6 mm ²	Copper conductor	Steel tape armour	3.08 Ω/km	33 mm	1.01 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Copper 10 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	5C	10 mm ²	Copper conductor	Steel tape armour	1.83 Ω/km	34 mm	1.23 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Copper 16 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	5C	16 mm ²	Copper conductor	Steel tape armour	1.15 Ω/km	36 mm	1.56 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Copper 25 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	5C	25 mm ²	Copper conductor	Steel tape armour	0.727 Ω/km	39 mm	2.06 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Copper 35 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	5C	35 mm ²	Copper conductor	Steel tape armour	0.524 Ω/km	41 mm	2.60 kg/m

Cable reference	Voltage class	Core layout	Cross-section	Conductor	Armour	Max DC resistance at 20 °C	OD guide	Weight guide
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Copper 50 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	5C	50 mm ²	Copper conductor	Steel tape armour	0.387 Ω/km	43 mm	3.43 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Copper 70 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	5C	70 mm ²	Copper conductor	Steel tape armour	0.268 Ω/km	46 mm	4.53 kg/m
Cable reference	Voltage class	Core layout	Cross-section	Conductor	Armour	Max DC resistance at 20 °C	OD guide	Weight guide
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Aluminium 16 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	16 mm ²	Aluminium conductor	Steel tape armour	1.91 Ω/km	29 mm	0.82 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Aluminium 25 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	25 mm ²	Aluminium conductor	Steel tape armour	1.20 Ω/km	32 mm	0.90 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Aluminium 35 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	35 mm ²	Aluminium conductor	Steel tape armour	0.868 Ω/km	34 mm	0.99 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Aluminium 50 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	50 mm ²	Aluminium conductor	Steel tape armour	0.641 Ω/km	36 mm	1.13 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Aluminium 70 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	70 mm ²	Aluminium conductor	Steel tape armour	0.443 Ω/km	39 mm	1.31 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Aluminium 95 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	95 mm ²	Aluminium conductor	Steel tape armour	0.320 Ω/km	42 mm	1.53 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Aluminium 120 mm ² Steel tape armour PVC outer sheath	0.6/1 kV	2C	120 mm ²	Aluminium conductor	Steel tape armour	0.253 Ω/km	45 mm	1.76 kg/m

Cable reference	Voltage class	Core layout	Cross-section	Conductor	Armour	Max DC resistance at 20 °C	OD guide	Weight guide
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Aluminium 150 mm² Steel tape armour PVC outer sheath	0.6/1 kV	2C	150 mm ²	Aluminium conductor	Steel tape armour	0.206 Ω/km	48 mm	2.03 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Aluminium 185 mm² Steel tape armour PVC outer sheath	0.6/1 kV	2C	185 mm ²	Aluminium conductor	Steel tape armour	0.164 Ω/km	51 mm	2.35 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 2C Aluminium 240 mm² Steel tape armour PVC outer sheath	0.6/1 kV	2C	240 mm ²	Aluminium conductor	Steel tape armour	0.125 Ω/km	55 mm	2.84 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Aluminium 16 mm² Steel tape armour PVC outer sheath	0.6/1 kV	3C	16 mm ²	Aluminium conductor	Steel tape armour	1.91 Ω/km	32 mm	0.90 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Aluminium 25 mm² Steel tape armour PVC outer sheath	0.6/1 kV	3C	25 mm ²	Aluminium conductor	Steel tape armour	1.20 Ω/km	34 mm	1.02 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Aluminium 35 mm² Steel tape armour PVC outer sheath	0.6/1 kV	3C	35 mm ²	Aluminium conductor	Steel tape armour	0.868 Ω/km	36 mm	1.15 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Aluminium 50 mm² Steel tape armour PVC outer sheath	0.6/1 kV	3C	50 mm ²	Aluminium conductor	Steel tape armour	0.641 Ω/km	38 mm	1.35 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Aluminium 70 mm² Steel tape armour PVC outer sheath	0.6/1 kV	3C	70 mm ²	Aluminium conductor	Steel tape armour	0.443 Ω/km	41 mm	1.62 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Aluminium 95 mm² Steel tape armour PVC outer sheath	0.6/1 kV	3C	95 mm ²	Aluminium conductor	Steel tape armour	0.320 Ω/km	44 mm	1.96 kg/m

Cable reference	Voltage class	Core layout	Cross-section	Conductor	Armour	Max DC resistance at 20 °C	OD guide	Weight guide
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Aluminium 120 mm² Steel tape armour PVC outer sheath	0.6/1 kV	3C	120 mm ²	Aluminium conductor	Steel tape armour	0.253 Ω/km	47 mm	2.30 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Aluminium 150 mm² Steel tape armour PVC outer sheath	0.6/1 kV	3C	150 mm ²	Aluminium conductor	Steel tape armour	0.206 Ω/km	50 mm	2.70 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Aluminium 185 mm² Steel tape armour PVC outer sheath	0.6/1 kV	3C	185 mm ²	Aluminium conductor	Steel tape armour	0.164 Ω/km	53 mm	3.18 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 3C Aluminium 240 mm² Steel tape armour PVC outer sheath	0.6/1 kV	3C	240 mm ²	Aluminium conductor	Steel tape armour	0.125 Ω/km	57 mm	3.92 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Aluminium 16 mm² Steel tape armour PVC outer sheath	0.6/1 kV	4C	16 mm ²	Aluminium conductor	Steel tape armour	1.91 Ω/km	34 mm	0.97 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Aluminium 25 mm² Steel tape armour PVC outer sheath	0.6/1 kV	4C	25 mm ²	Aluminium conductor	Steel tape armour	1.20 Ω/km	36 mm	1.13 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Aluminium 35 mm² Steel tape armour PVC outer sheath	0.6/1 kV	4C	35 mm ²	Aluminium conductor	Steel tape armour	0.868 Ω/km	38 mm	1.31 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Aluminium 50 mm² Steel tape armour PVC outer sheath	0.6/1 kV	4C	50 mm ²	Aluminium conductor	Steel tape armour	0.641 Ω/km	41 mm	1.58 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Aluminium 70 mm² Steel tape armour PVC outer sheath	0.6/1 kV	4C	70 mm ²	Aluminium conductor	Steel tape armour	0.443 Ω/km	44 mm	1.94 kg/m

Cable reference	Voltage class	Core layout	Cross-section	Conductor	Armour	Max DC resistance at 20 °C	OD guide	Weight guide
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Aluminium 95 mm² Steel tape armour PVC outer sheath	0.6/1 kV	4C	95 mm ²	Aluminium conductor	Steel tape armour	0.320 Ω/km	47 mm	2.39 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Aluminium 120 mm² Steel tape armour PVC outer sheath	0.6/1 kV	4C	120 mm ²	Aluminium conductor	Steel tape armour	0.253 Ω/km	49 mm	2.84 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Aluminium 150 mm² Steel tape armour PVC outer sheath	0.6/1 kV	4C	150 mm ²	Aluminium conductor	Steel tape armour	0.206 Ω/km	52 mm	3.38 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Aluminium 185 mm² Steel tape armour PVC outer sheath	0.6/1 kV	4C	185 mm ²	Aluminium conductor	Steel tape armour	0.164 Ω/km	55 mm	4.01 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 4C Aluminium 240 mm² Steel tape armour PVC outer sheath	0.6/1 kV	4C	240 mm ²	Aluminium conductor	Steel tape armour	0.125 Ω/km	59 mm	5.00 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Aluminium 16 mm² Steel tape armour PVC outer sheath	0.6/1 kV	5C	16 mm ²	Aluminium conductor	Steel tape armour	1.91 Ω/km	36 mm	1.04 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Aluminium 25 mm² Steel tape armour PVC outer sheath	0.6/1 kV	5C	25 mm ²	Aluminium conductor	Steel tape armour	1.20 Ω/km	39 mm	1.24 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Aluminium 35 mm² Steel tape armour PVC outer sheath	0.6/1 kV	5C	35 mm ²	Aluminium conductor	Steel tape armour	0.868 Ω/km	41 mm	1.47 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Aluminium 50 mm² Steel tape armour PVC outer sheath	0.6/1 kV	5C	50 mm ²	Aluminium conductor	Steel tape armour	0.641 Ω/km	43 mm	1.81 kg/m

Cable reference	Voltage class	Core layout	Cross-section	Conductor	Armour	Max DC resistance at 20 °C	OD guide	Weight guide
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Aluminium 70 mm² Steel tape armour PVC outer sheath	0.6/1 kV	5C	70 mm ²	Aluminium conductor	Steel tape armour	0.443 Ω/km	46 mm	2.26 kg/m
XLPE/STA/PVC armoured cable 0.6/1 kV 5C Aluminium 95 mm² Steel tape armour PVC outer sheath	0.6/1 kV	5C	95 mm ²	Aluminium conductor	Steel tape armour	0.320 Ω/km	49 mm	2.82 kg/m

UE Cable · China — sales@uecable.com · uecable.com Confirm colour, printing, packing length, delivery country and test documents on enquiry.